



WORTHINGTON PLANK & HERRINGBONE

Technical Specifications

DESCRIPTION:	ENGINEERED HARDWOOD FLOORING
SPECIES:	OAK
SURFACE TEXTURE:	WIRE BRUSHED
CORE:	PLYWOOD
VENEER CUT:	SAWN FACE
VENEER THICKNESS:	3.0MM
WARRANTY:	7 YEAR COMMERCIAL WARRANTY
INSTALLATION:	STAPLE, FLOAT, GLUE
DIMENSIONS:	1/2" X 5" WIDTH X RANDOM LENGTH UP TO 72" (ALSO AVAILABLE IN HERRINGBONE 5"X 20", FIXED LENGTHS, 10,800 SQFT. MINIMUM FROM FACTORY. 10 WEEK LEAD TIME)
PACKAGING:	14.76 SF/CTN, 49 CTN/PLT, 723.43 SF/PLT, 27 PLTS/40' CONTAINER, 19,532.64SF/CONTAINER
PROFILE:	T&G
BEVEL:	MICRO-BEVEL
HARDNESS:	OAK-1360
WEAR LAYER FINISH:	UV CURED URETHANE W/ ALUMINUM OXIDE
GLOSS LEVEL:	LOW
CERTIFICATIONS:	CARB II, LACEY ACT COMPLIANT, FLOORSCORE®, FSC AVAILABLE
COUNTRY OF HARVEST:	OAK-EUROPE
COUNTRY OF ORIGIN:	MANUFACTURED IN INDONESIA

NATURAL COLOR VARIATION IN RAW MATERIALS WILL DICTATE THE FINAL SHADE OF STAIN AS EVERY TREE PROVIDES UNIQUE AND NATURAL CHARACTERISTICS. INSTALLED FLOOR MAY VARY FROM SAMPLE/PICTURE.

