

URBBA

MONTAUK TECHNICAL SPECIFICATIONS

DESCRIPTION:	ENGINEERED HARDWOOD FLOORING
CORE	PLYWOOD CORE
SPECIES:	HICKORY, OAK
SURFACE TEXTURE:	WIRE BRUSHED
VENEER CUT:	SLICED
VENEER THICKNESS:	2.0MM
WARRANTY:	5 YEAR COMMERCIAL WARRANTY
INSTALLATION:	STAPLE, FLOAT, GLUE
DIMENSIONS:	1/2" X 7.5" X RANDOM LENGTHS UP TO 82" (NOMINAL)
PACKAGING:	25.77 SF/CTN, 55 CTN/PLT, 1417.4 SF/PLT, 2464 LBS/PLT
PROFILE:	T&G
BEVEL:	MICRO BEVEL
HARDNESS:	HICKORY-1813, OAK-1360
WEAR LAYER FINISH:	UV CURED URETHANE W/ ALUMINUM OXIDE
GLOSS LEVEL:	LOW
CERTIFICATIONS:	CARB II, LACEY ACT COMPLIANT, FLOORSCORE®, FSC AVAILABLE
COUNTRY OF HARVEST:	HICKORY – USA ~ OAK – CHINA
COUNTRY OF ORIGIN:	MANUFACTURED IN CHINA

NATURAL COLOR VARIATION IN RAW MATERIALS WILL DICTATE THE FINAL SHADE OF STAIN, AS EVERY TREE PROVIDES UNIQUE AND NATURAL CHARACTERISTICS. INSTALLED FLOOR MAY VARY FROM SAMPLE OR PICTURES.

