

# URBBA

## PIER PLANK TECHNICAL SPECIFICATIONS

DESCRIPTION:	ENGINEERED HARDWOOD WATERPROOF FLOORING
SPECIES:	HICKORY, OAK & BIRCH
SURFACE TEXTURE:	HICKORY - HAND SCRAPED, OAK & BIRCH - WIRE BRUSHED
CORE:	4MM SPC
VENEER THICKNESS:	1.2MM
WARRANTY:	5 YEAR LIGHT COMMERCIAL WARRANTY
INSTALLATION:	FLOAT, GLUE
INSTALLATION LEVEL:	ALL
SUBFLOOR TYPE:	WOOD OR CONCRETE
DIMENSIONS:	HICKORY - 5.2MM X 5" X RANDOM LENGTHS UP TO 48" OAK & BIRCH - 6.2MM X 6.5" X RANDOM LENGTHS UP TO 72"
PACKAGING:	HICKORY - 26.47SF/CTN, 36CTN/PLT, 952.92SF/PLT, 1935LBS/PLT OAK & BIRCH - 32.32SF/CTN, 42CTN/PLT, 1357.44SF/PLT, 2757LBS/PLT
PROFILE:	LOCKING
BEVEL:	MICRO BEVEL
HARDNESS:	HICKORY-1813, OAK-1360, BIRCH- 1260
WEAR LAYER FINISH:	UV CURED URETHANE W/ALUMINUM OXIDE
BACKING:	ATTACHED 1MM IXPE ON OAK AND BIRCH
GLOSS LEVEL:	LOW
WATERPROOF:	YES
TESTING METHOD:	S EN 31 AND BS EN 13329
SOUND RATING:	PASS
TEST METHOD:	E ASTM 2179
IIC NO BACKING:	45
IIC W/BACKING:	52
CERTIFICATIONS:	CARB 2, LACEY ACT COMPLIANT, FLOORSCORE®, FSC AVAILABLE
COUNTRY OF HARVEST:	HICKORY – USA ~ OAK & BIRCH - CHINA
COUNTRY OF ORIGIN:	MANUFACTURED IN CHINA

NATURAL COLOR VARIATION IN RAW MATERIALS WILL DICTATE THE FINAL SHADE OF STAIN, AS EVERY TREE PROVIDES UNIQUE AND NATURAL CHARACTERISTICS. INSTALLED FLOOR MAY VARY FROM SAMPLE OR PICTURES.

